

Web Services Technical Integration Guide to Price and Delivey Time Calculator System – Sistema Calculador de Preço e Prazo – SCPP

**Brasília
2021**

Version 2.2 of 03/26/2021

Parcels price and delivery time calculator

Correios price and delivery time calculator is intended for clients who have a SEDEX and PAC contract and need to calculate, in their environment and in a personalized way, the price and delivery time of a parcel. For the calculation agreed in the contract, clients must necessarily inform in each consultation the administrative code, password and code of one or more services inherent to their contract.

It is also possible for a customer who does not have a contract with Correios to carry out the calculation, however, in this case, the prices shown will be those charged at the branch counter.

In order to give greater flexibility to the client, Correios offers four ways to obtain query's result:

- a) **Webservice query:** This form of query uses the Web Services technology - collection of protocols and standards (XML, SOAP and WSDL) used to exchange information between Internet applications. It is suitable for advanced users, who master this technology;
- b) **XML format result:** In this form of query, the parameters are passed to the price and delivery time calculator via post and the result is returned in XML format;
- c) **Result on client's page:** In this form of query, the parameters are passed to the price and delivery time calculator via post and the result is returned on an HTML page specified by the requester.

Ex: `<input type=hidden name="Resposta" value= "http://www.seusite.com.br/suapagina.xxx">`

**** E.g:* `<input type=hidden name= "Answer" value = "http://www.yoursite.com/youpage.xxx">`

1. Query via Webservice:

WebService interface can be found at:

<http://ws.correios.com.br/calculador/CalcPrecoPrazo.asmx?wsdl>

Recommended apps for testing:

- SOAP UI;
- Browser plug-ins or extensions.

The methods related to this manual are:

- **CalcPrecoPrazo:** returns the price and the delivery time of a parcel.
- **CalcPreco:** returns the shipping price of a parcel.
- **CalcPrazo:** returns the delivery time of a parcel.

1.1 Input parameters: **CalcPrecoPrazo** method

Tag	Type	Description	Mandatory												
nCdEmpresa	String	Your administrative code with Correios. The code is available in the contract's draft signed with Correios.	Yes, for contract clients. For clients without a contract, inform the empty parameter.												
sDsSenha	String	Password for accessing the service, associated to your administrative code. The initial password corresponds to the CNPJ's first 8 digits previously informed in the contract. .	Yes, for contract clients. For clients without a contract, inform the empty parameter.												
nCdServico	String	<p>For customers without a contract:</p> <p>Current Codes:</p> <table border="1"> <thead> <tr> <th>Code</th> <th>Service</th> </tr> </thead> <tbody> <tr> <td>04014</td> <td>SEDEX à vista</td> </tr> <tr> <td>04510</td> <td>PAC à vista</td> </tr> <tr> <td>04782</td> <td>SEDEX 12 (à vista)</td> </tr> <tr> <td>04790</td> <td>SEDEX 10 (à vista)</td> </tr> <tr> <td>04804</td> <td>SEDEX Hoje à vista</td> </tr> </tbody> </table> <p>For clients with contract: Consult the codes in your contract.</p>	Code	Service	04014	SEDEX à vista	04510	PAC à vista	04782	SEDEX 12 (à vista)	04790	SEDEX 10 (à vista)	04804	SEDEX Hoje à vista	Yes
Code	Service														
04014	SEDEX à vista														
04510	PAC à vista														
04782	SEDEX 12 (à vista)														
04790	SEDEX 10 (à vista)														
04804	SEDEX Hoje à vista														
sCepOrigem	String	Origin ZIP Code of without hyphen. Example: 05311900	Yes												
sCepDestino	String	Destination ZIP Code without hyphen.	Yes												
nVIPeso	String	Parcel's weight, including its packaging. The weight must be entered in kilograms. If the format is an envelope, the maximum allowed value will be 1kg.	Yes												

nCdFormato	Int	Parcel format (including packaging). Possible values: 1, 2 or 3 1 - Box / package format 2 - Roll / prism format 3 - Envelope	Yes
nVIComprimento	Decimal	Parcel length (including packaging), in centimeters.	Yes
nVIAltura	Decimal	Parcel height (including packaging), in centimeters. If the format is an envelope, enter zero (0).	Yes
nVILargura	Decimal	Parcel width (including packaging), in centimeters.	Yes
nVIDiametro	Decimal	Parcel diameter (including packaging), in centimeters.	Yes
sCdMaoPropria	String	Indicates whether the parcel will be delivered with the additional service Restricting Delivery. Possible values: Y or N (Y - Yes, N - No)	Yes
nVIValorDeclarado	Decimal	Indicates whether the parcel will be delivered with the additional service Declared Value. In this field, the desired declared value must be presented, in Reais.	Yes. If you do not choose the service, enter zero (0)
sCdAvisoRecebimento	String	Indicates whether the parcel will be delivered with the additional service Return Receipt. Possible values: Y or N (Y - Yes, N - No)	Yes. If you do not choose the service, enter No 'N'

Data return

The data return is an XML informing the query's status and a list (array) with the price and the delivery time of SEDEX and PAC services.

Parameter	Description
Resultado.Servicos	Array with the prices and delivery time of the requested and available services.
Resultado.Servicos.cServico[x].Codigo	Delivery Service Code.
Resultado.Servicos.cServico[x].Valor	Parcel total price, in Reais, including optional services prices.
Resultado.Servicos.cServico[x].PrazoEntrega	Estimated time in days for the product delivery. If the returned value is 0 (zero), it indicates that the delivery time was not returned correctly.
Resultado.Servicos.cServico[x].ValorMaoPropria	Price of additional service Restricting Delivery.
Resultado.Servicos.cServico[x].ValorAvisoRecebimento	Price of additional service Return Receipt.
Resultado.Servicos.cServico[x].ValorValorDeclarado	Price of additional service Declared Value.
Resultado.Servicos.cServico[x].EntregaDomiciliar	Informs if the locality has home delivery. If the delivery time is not returned correctly, the return for this parameter will be empty.
Resultado.Servicos.cServico[x].EntregaSabado	Informs if the locality has home delivery on Saturdays. If the delivery time is not returned correctly, the return for this parameter will be empty.
Resultado.Servicos.cServico[x].Erro	<Error codes returned by the calculator> + code 7 (Service unavailable, try later)
Resultado.Servicos.cServico[x].MsgErro	Returns the generated error description.

XML return example

```

<?xml version="1.0" encoding="UTF-8"?>
- <cResultado xmlns="http://tempuri.org/" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  - <Servicos>
    - <cServico>
      <Codigo>4510</Codigo>
      <Valor>25,70</Valor>
      <PrazoEntrega>6</PrazoEntrega>
      <ValorMaoPropria>0,00</ValorMaoPropria>
      <ValorAvisoRecebimento>0,00</ValorAvisoRecebimento>
      <ValorValorDeclarado>0,00</ValorValorDeclarado>
      <EntregaDomiciliar>S</EntregaDomiciliar>
      <EntregaSabado>N</EntregaSabado>
      <Erro>0</Erro>
      <MsgErro/>
      <ValorSemAdicionais>25,70</ValorSemAdicionais>
      <obsFim/>
    </cServico>
  </Servicos>
</cResultado>

```

1.2 Input parameters: CalcPreco method

Tag	Type	Description	Mandatory												
nCdEmpresa	String	Your administrative code with Correios. The code is available in the contract's draft signed with Correios.	Yes, for contract clients. For clients without a contract, inform the empty parameter.												
sDsSenha	String	Password for accessing the service, associated to your administrative code. The initial password corresponds to the CNPJ's first 8 digits previously informed in the contract.	Yes, for contract clients. For clients without a contract, inform the empty parameter.												
nCdServico	String	<p>For customers without a contract:</p> <p>Current Codes:</p> <table border="1"> <thead> <tr> <th>Code</th> <th>Service</th> </tr> </thead> <tbody> <tr> <td>04014</td> <td>SEDEX à vista</td> </tr> <tr> <td>04510</td> <td>PAC à vista</td> </tr> <tr> <td>04782</td> <td>SEDEX 12 (à vista)</td> </tr> <tr> <td>04790</td> <td>SEDEX 10 (à vista)</td> </tr> <tr> <td>04804</td> <td>SEDEX Hoje à vista</td> </tr> </tbody> </table> <p>For clients with contract: Consult the codes in your contract.</p>	Code	Service	04014	SEDEX à vista	04510	PAC à vista	04782	SEDEX 12 (à vista)	04790	SEDEX 10 (à vista)	04804	SEDEX Hoje à vista	Yes
Code	Service														
04014	SEDEX à vista														
04510	PAC à vista														
04782	SEDEX 12 (à vista)														
04790	SEDEX 10 (à vista)														
04804	SEDEX Hoje à vista														
sCepOrigem	String	Origin ZIP Code without hyphen. Example: 05311900	Yes												
sCepDestino	String	Destination ZIP Code without hyphen.	Yes												
nVIPeso	String	Parcel's weight, including its packaging. The weight must be entered in kilograms. If the format is an envelope, the maximum allowed value will be 1kg.	Yes												
nCdFormato	Int	Parcel format (including packaging). Possible values: 1, 2 or 3 1 - Box / package format 2 - Roll / prism format 3 - Envelope	Yes												
nVIComprimento	Decimal	Parcel length (including packaging), in centimeters.	Yes												
nVIAltura	Decimal	Parcel height (including packaging), in centimeters. If the format is an envelope, enter zero (0).	Yes												
nVILargura	Decimal	Parcel width (including packaging), in centimeters.	Yes												
nVIDiametro	Decimal	Parcel diameter (including packaging), in centimeters.	Yes												
sCdMaoPropria	String	Indicates whether the parcel will be delivered with the additional service Restricting Delivery. Possible values: Y or N (Y - Yes, N - No)	Yes												
nVIValorDeclarado	Decimal	Indicates whether the parcel will be delivered with the additional service Declared Value. In this field, the desired declared value must be presented, in Reais.	Yes. If you do not choose the service, enter zero (0)												

sCdAvisoRecebimento	String	Indicates whether the parcel will be delivered with the additional service Return Receipt. Possible values: Y or N (Y - Yes, N - No)	Yes. If you do not choose the service, enter No 'N'
---------------------	--------	---	--

Data return

The data return is an XML informing the query's status and a list (array) with the price of SEDEX and PAC services.

Parameter	Description
Resultado.Servicos	Array with the prices and delivery time of the requested and available services.
Resultado.Servicos.cServico[x].Codigo	Delivery Service Code.
Resultado.Servicos.cServico[x].Valor	Parcel total price, in Reais, including optional services prices.
Resultado.Servicos.cServico[x].ValorMaoPropria	Price of additional service Restricting Delivery.
Resultado.Servicos.cServico[x].ValorAvisoRecebimento	Price of additional service Return Receipt.
Resultado.Servicos.cServico[x].ValorValorDeclarado	Price of additional service Declared Value.
Resultado.Servicos.cServico[x].Erro	<Error codes returned by the calculator> + code 7 (Service unavailable, try later)
Resultado.Servicos.cServico[x].MsgErro	Returns the generated error description.

XML return example

```
<?xml version="1.0" encoding="UTF-8"?>
- <cResultado xmlns="http://tempuri.org/" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  - <Servicos>
    - <cServico>
      <Codigo>4510</Codigo>
      <Valor>25,70</Valor>
      <ValorMaoPropria>0,00</ValorMaoPropria>
      <ValorAvisoRecebimento>0,00</ValorAvisoRecebimento>
      <ValorValorDeclarado>0,00</ValorValorDeclarado>
      <Erro/>
      <MsgErro/>
      <ValorSemAdicionais>25,70</ValorSemAdicionais>
    </cServico>
  </Servicos>
</cResultado>
```

1.3 Input parameters: CalcPrazo method

Tag	Type	Description	Mandatory												
sCepOrigem	String	Origin ZIP Code without hyphen. Example: 05311900	Yes												
sCepDestino	String	Destination ZIP Code without hyphen.	Yes												
nCdServico	String	<p>For customers without a contract:</p> <p>Current Codes:</p> <table border="1"> <thead> <tr> <th>Code</th> <th>Service</th> </tr> </thead> <tbody> <tr> <td>04014</td> <td>SEDEX à vista</td> </tr> <tr> <td>04510</td> <td>PAC à vista</td> </tr> <tr> <td>04782</td> <td>SEDEX 12 (à vista)</td> </tr> <tr> <td>04790</td> <td>SEDEX 10 (à vista)</td> </tr> <tr> <td>04804</td> <td>SEDEX Hoje à vista</td> </tr> </tbody> </table> <p>For clients with contract: Consult the codes in your contract.</p>	Code	Service	04014	SEDEX à vista	04510	PAC à vista	04782	SEDEX 12 (à vista)	04790	SEDEX 10 (à vista)	04804	SEDEX Hoje à vista	Yes
Code	Service														
04014	SEDEX à vista														
04510	PAC à vista														
04782	SEDEX 12 (à vista)														
04790	SEDEX 10 (à vista)														
04804	SEDEX Hoje à vista														

Data return

The data return is an XML informing the query's status and a list (array) with the delivery time of SEDEX and PAC services.

Parâmetro	Descrição
Resultado.Servicos	Array with the prices and delivery time of the requested and available services.
Resultado.Servicos.cServico[x].Codigo	Delivery Service Code.
Resultado.Servicos.cServico[x].PrazoEntrega	Estimated time in days for the product delivery. If the returned value is 0 (zero), it indicates that the delivery time was not returned correctly.
Resultado.Servicos.cServico[x].EntregaDomiciliar	Informs if the locality has home delivery. If the delivery time is not returned correctly, the return for this parameter will be empty.
Resultado.Servicos.cServico[x].EntregaSabado	Informs if the locality has home delivery on Saturdays. If the delivery time is not returned correctly, the return for this parameter will be empty.
Resultado.Servicos.cServico[x].Erro	<Error codes returned by the calculator> + code 7 (Service unavailable, try later)
Resultado.Servicos.cServico[x].MsgErro	Returns the generated error description.

XML return example

```
<?xml version="1.0" encoding="UTF-8"?>
- <cResultado xmlns="http://tempuri.org/" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  - <Servicos>
    - <cServico>
      <Codigo>4510</Codigo>
      <PrazoEntrega>6</PrazoEntrega>
      <EntregaDomiciliar>S</EntregaDomiciliar>
      <EntregaSabado>N</EntregaSabado>
      <Erro/>
      <MsgErro/>
      <obsFim/>
    </cServico>
  </Servicos>
</cResultado>
```

Query example with return in XML format for price and delivery time:

<http://ws.correios.com.br/calculador/CalcPrecoPrazo.aspx?nCdBateria=08082650&sDsSenha=564321&sCepOrigem=70002900&sCepDestino=04547000&nVIPeso=1&nCdFormato=1&nVIComprimento=20&nVIAltura=20&nVILargura=20&sCdMaoPropria=n&nVIValorDeclarado=0&sCdAvisoRecebimento=n&nCdServico=04510&nVIDiametro=0&StrRetorno=xml&nIndicaCalculo=3>

Return example in XML format

```
<?xml version="1.0" encoding="ISO-8859-1"?>
- <Servicos>
  - <cServico>
    <Codigo>04510</Codigo>
    <Valor>22,90</Valor>
    <PrazoEntrega>6</PrazoEntrega>
    <ValorSemAdicionais>22,90</ValorSemAdicionais>
    <ValorMaoPropria>0,00</ValorMaoPropria>
    <ValorAvisoRecebimento>0,00</ValorAvisoRecebimento>
    <ValorValorDeclarado>0,00</ValorValorDeclarado>
    <EntregaDomiciliar>S</EntregaDomiciliar>
    <EntregaSabado>N</EntregaSabado>
    <Erro>0</Erro>
    <MsgErro/>
  </cServico>
</Servicos>
```

2. Error codes and messages:

Error code	Error message
0	Successful processing
-1	Invalid service code
-2	Invalid origin ZIP Code
-3	Invalid destination ZIP Code
-4	Exceeded weight
-5	The Declared Value must not exceed R\$ 10.000,00
-6	Service unavailable for the informed area
-7	The Declared Value is mandatory for this service
-8	This service does not accept Restricting Delivery
-9	This service does not accept Return Receipt
-10	Pricing unavailable for the informed area
-11	To define the price, the length, width and height of the object must also be informed, in centimeters (cm)
-12	Invalid length
-13	Invalid width
-14	Invalid height
-15	The length cannot be greater than 105 cm
-16	The width cannot be greater than 105 cm
-17	The height cannot be greater than 105 cm
-18	The height cannot be smaller than 2 cm
-20	The width cannot be smaller than 11 cm
-22	The length cannot be smaller than 16 cm
-23	The resulting sum of length + width + height must not exceed 200 cm
-24	Invalid length
-25	Invalid diameter
-26	Enter the length
-27	Enter the diameter
-28	The length cannot be greater than 105 cm
-29	The diameter cannot be greater than 91 cm
-30	The length cannot be smaller than 18 cm
-31	The diameter cannot be smaller than 5 cm
-32	The resulting sum of length + twice the diameter must not exceed 200 cm
-33	System temporarily down. Please try later
-34	Invalid Administrative Code or Password

-35	Incorrect password
-36	Client has no current contract with Correios
-37	Client does not have an active service in its contract
-38	Service unavailable for this administrative code
-39	Exceeded weight for envelope format
-40	To define the price, the length, width and height of the object must also be informed, in centimeters (cm)
-41	The length cannot be greater than 60 cm
-42	The length cannot be smaller than 16 cm
-43	The resulting sum of length + width must not exceed 120 cm
-44	The width cannot be smaller than 11 cm
-45	The width cannot be greater than 60 cm
-888	Error calculating the tariff
006	Place of origin does not cover the informed service
007	Destination location does not cover the informed service
008	Service unavailable for the informed area
009	Initial ZIP Code belonging to the Risk Area
010	Destination ZIP Code is temporarily out of home delivery. Delivery will be made to the branch indicated in the Arrival Notice, which will be delivered to the address of the recipient
011	Destination ZIP Code is subject to special delivery conditions by ECT(Correios) and will be carried out with the addition of up to 7 (seven) working days to the regular term
7	Service unavailable, try later
99	Other miscellaneous .Net errors

3. Example of a client application for querying prices and delivery times via webservice:

Steps for Use:

To test copy the source code examples to a web server at wwwroot with the names frete.asp and e frete2.asp respectively.

Source Codes:

Frete.asp – Call Form

```
<html>
<body>
<form name="frm" action="frete2.asp" method="post" ID="Form1">
  <fieldset style="background: EEEEE;">
    <legend>Calculo de Frete</legend>
    <div>
      <span style="width:130px;">Codigo:</span>
      <span><input type="text" name="codigo" value=""></span>
    </div>
    <div>
      <span style="width:130px;">Senha:</span>
      <span><input type="password" name="senha" value=""></span>
    </div>
    <div>
      <span style="width:130px;">Serviços:</span>
      <span><input type="text" name="servicos" value=""></span>
    </div>
    <div>
      <span style="width:130px;">Cep Origem:</span>
      <span><input type="text" name="cepori" value=""></span>
    </div>
    <div>
      <span style="width:130px;">Cep Destino:</span>
      <span><input type="text" name="cepdes" value=""></span>
    </div>
    <div>
      <span style="width:130px;">Peso:</span>
      <span><input type="text" name="peso" value=""></span>
    </div>
    <div>
      <span style="width:130px;">Formato:</span>
      <span><select name="formato" size="1">
        <option value="1">Caixa/pacote</option>
        <option value="2">Rolo/prisma</option>
      </select>
    </span>
    </div>
    <div>
      <span style="width:130px;">Comprimento:</span>
      <span><input type="text" name="comprimento" value=""></span>
    </div>
    <div>
      <span style="width:130px;">Altura:</span>
      <span><input type="text" name="altura" value=""></span>
    </div>
    <div>
      <span style="width:130px;">Largura:</span>
      <span><input type="text" name="largura" value=""></span>
    </div>
    <div>
      <span style="width:130px;">Diâmetro:</span>
      <span><input type="text" name="diametro" value=""></span>
    </div>
    <div>
      <span style="width:130px;">Mão própria:</span>
      <span><select name="maopropria" size="1">
        <option value="S">Sim</option>
      </select>
    </span>
    </div>
  </fieldset>
</form>
</body>
</html>
```

```

        <option value="N">Não</option>
    </select>
    </span>
</div>
<div>
    <span style="width:130px;">Valor declarado:</span>
    <span><input type="text" name="valordeclarado" value=""></span>
</div>
<div>
    <span style="width:130px;">Aviso de Recebimento:</span>
    <span><select name="avisorecebimento" size="1">
        <option value="S">Sim</option>
        <option value="N">Não</option>
    </select>
    </span>
</div>

<div>
    <span><input type="SUBMIT" name="BTN" value="Consultar"
ID="Submit1"></span>
</div>

</fieldset>
</form>
</body>

</html>

```

Frete2.asp – Data Request

```

<%@LANGUAGE=VBScript%>
<%
option explicit
'On Error Resume Next
dim oXmlHttp, oXmlDom
dim sReturn, sPacoteSoap
dim nCodigoRet, sDescricaoRet
set oXmlHttp = server.CreateObject("Microsoft.XMLHTTP")
const sSoapServer = "http://ws.correios.com.br/calculador/CalcPrecoPrazo.asmx"

'Tratamento de campos obrigatórios
dim peso, comprimento, altura, largura, diametro, valordeclarado
if request.form("peso") = "" then
    peso = "0"
else
    peso = request.form("peso")
end if

if request.form("comprimento") = "" then
    comprimento = "0"
else
    comprimento = request.form("comprimento")
end if

if request.form("altura") = "" then
    altura = "0"
else
    altura = request.form("altura")
end if

if request.form("largura") = "" then
    largura = "0"
else
    largura = request.form("largura")
end if

if request.form("diametro") = "" then
    diametro = "0"
else
    diametro = request.form("diametro")
end if

if request.form("valordeclarado") = "" then
    valordeclarado = "0"
else

```

```

        valordeclarado = request.form("valordeclarado")
    end if

    sPacoteSoap =
    GerarPacoteSoap(request.form("codigo"), request.form("senha"), request.form("servicos"), request.form("cepори"), request.form("cepdes"), peso, request.form("formato"), comprimento, altura, largura, diametro, request.form("maopropria"), valordeclarado, request.form("avisorecebimento"))
    oXmlHttp.open "POST", sSoapServer, false
    oXmlHttp.setRequestHeader "SOAPAction", "http://tempuri.org/CalcPrecoPrazo"
    oXmlHttp.setRequestHeader "Content-Type", "text/xml; charset=utf-8"
    oXmlHttp.send(sPacoteSoap)
    sReturn = oXmlHttp.responseText
    'parse xml
    Set oXmlDom = Server.CreateObject("Microsoft.XMLDOM")
    oXmlDom.loadXML sReturn
    set oXmlDom =
    oXmlDom.selectSingleNode("soap:Envelope/soap:Body/CalcPrecoPrazoResponse/CalcPrecoPrazoResult")
    'Se o retorno foi OK então listar os fretes disponíveis
    dim oNodes, oNode
    'Seleciona os fretes no XML
    Set oNodes = oXmlDom.selectNodes("Servicos/cServico")
    'Mostra todos os fretes disponíveis
    for each oNode in oNodes
        Response.Write "<div><span style=width:150px;>Código:</span><span>" &
        oNode.selectSingleNode("Codigo").Text & "</span><br>"
        Response.Write "<span style=width:150px;>Valor:</span><span>" &
        oNode.selectSingleNode("Valor").Text & "</span><br>"
        Response.Write "<span style=width:150px;>Prazo: </span><span>" &
        oNode.selectSingleNode("PrazoEntrega").Text & "</span></div>"
        Response.Write "<span style=width:150px;>Valor Mão Própria: </span><span>" &
        oNode.selectSingleNode("ValorMaoPropria").Text & "</span></div>"
        Response.Write "<span style=width:150px;>Valor Aviso de Recebimento:
    </span><span>" & oNode.selectSingleNode("ValorAvisoRecebimento").Text & "</span></div>"
        Response.Write "<span style=width:150px;>Valor Valor Declarado: </span><span>" &
        oNode.selectSingleNode("ValorValorDeclarado").Text & "</span></div>"
        Response.Write "<span style=width:150px;>Entrega Domiciliar: </span><span>" &
        oNode.selectSingleNode("EntregaDomiciliar").Text & "</span></div>"
        Response.Write "<span style=width:150px;>Entrega Sábado: </span><span>" &
        oNode.selectSingleNode("EntregaSabado").Text & "</span></div>"
    next
    Set oXmlDom = Nothing
    function GerarPacoteSoap(nCdEmpresa, sDsSenha, nCdServico, sCepOrigem, sCepDestino, nVlPeso, nCdFormato, nVlComprimento, nVlAltura, nVlLargura, nVlDiametro, sCdMaoPropria, nVlValorDeclarado, sCdAvisoRecebimento)
        dim sSoap
        sSoap = "<?xml version=""1.0"" encoding=""utf-8""?>"
        sSoap = sSoap & "<soap:Envelope xmlns:xsi=""http://www.w3.org/2001/XMLSchema-instance"" xmlns:xsd=""http://www.w3.org/2001/XMLSchema""
    xmlns:soap=""http://schemas.xmlsoap.org/soap/envelope/"">"
        sSoap = sSoap & "<soap:Body>"
        sSoap = sSoap & "<CalcPrecoPrazo xmlns=""http://tempuri.org/"">"
        sSoap = sSoap & "<nCdEmpresa>" & nCdEmpresa & "</nCdEmpresa>"
        sSoap = sSoap & "<sDsSenha>" & sDsSenha & "</sDsSenha>"
        sSoap = sSoap & "<nCdServico>" & nCdServico & "</nCdServico>"
        sSoap = sSoap & "<sCepOrigem>" & sCepOrigem & "</sCepOrigem>"
        sSoap = sSoap & "<sCepDestino>" & sCepDestino & "</sCepDestino>"
        sSoap = sSoap & "<nVlPeso>" & nVlPeso & "</nVlPeso>"
        sSoap = sSoap & "<nCdFormato>" & nCdFormato & "</nCdFormato>"
        sSoap = sSoap & "<nVlComprimento>" & nVlComprimento & "</nVlComprimento>"
        sSoap = sSoap & "<nVlAltura>" & nVlAltura & "</nVlAltura>"
        sSoap = sSoap & "<nVlLargura>" & nVlLargura & "</nVlLargura>"
        sSoap = sSoap & "<nVlDiametro>" & nVlDiametro & "</nVlDiametro>"
        sSoap = sSoap & "<sCdMaoPropria>" & sCdMaoPropria & "</sCdMaoPropria>"
        sSoap = sSoap & "<nVlValorDeclarado>" & nVlValorDeclarado & "</nVlValorDeclarado>"
        sSoap = sSoap & "<sCdAvisoRecebimento>" & sCdAvisoRecebimento &
    "</sCdAvisoRecebimento>"
        sSoap = sSoap & "</CalcPrecoPrazo>"
        sSoap = sSoap & "</soap:Body>"
        sSoap = sSoap & "</soap:Envelope>"
        GerarPacoteSoap = sSoap
    end function
    %>
    <input type=""button"" name=""btn"" value=""Voltar"" onclick=""history.go(-1);"" ID=""Button1"">

```

For questions or information call our Customer Service Center – Phone + **55 11 3003-0888**.